



Thin and flexible metal foil tape backed by a conductive filler adhesive

#### Feature

- Highly conductive adhesive provides high shielding effectiveness.
- Easy punching and half-cutting to optimal configurations.

#### Material

- Base material / CCT-C : Copper foil  
CCT-A : Aluminum foil
- Adhesive layer / Conductive adhesive
- Standard length: 20m

※ Custom cutting is available upon request.

Part No.	Width (mm)	Thickness (mm)	adhesive strength	Resistivity
CCT-8-C	8	0.075	9.4N/25mm	0.004 $\Omega/\text{inch}^2$
CCT-10-C	10			
CCT-13-C	13			
CCT-20-C	20			
CCT-25-C	25			
CCT-50-C	50			
CCT-100-C	100			
CCT-600-C	600			
CCT-250-C* <sup>1</sup>	(□250)			
CCT-A4-C* <sup>1</sup>	(A4)			
CCT-6-A	6	0.09	8.6N/25mm	0.008 $\Omega/\text{inch}^2$
CCT-8-A	8			
CCT-15-A	15			
CCT-20-A	20			
CCT-25-A	25			
CCT-A4-A* <sup>1</sup>	(A4)			

※ 1) Sheet type

※ The values are measured data for reference, not guaranteed.