



Easy fastening lock

Releasable cable clamp with minimum protrusion on panel

Features

- Equipped with a new lock for easy fastening and unfastening.
- Dismounted without any tools required.

Material



- Nylon 66 (Color : Natural[※])

UL94 V-0



※ Color of RBWS-1TD-V0BK is black.



RBWS-D



RBWS-1TD-V0 BK



Part No.	A	B	C	D	(E)	Mounting hole size	Panel thickness	Std. Package
UL RBWS-0406D VO	1.5	6	4.5	3.7	17.13	Refer to Specification drawing	0.5~1.6	500 pcs.
UL RBWS-0510D VO		10	5.0	4.7	21.61			
UL RBWS-1015D VO	1.8	15	6.0	9.7	31.35			
UL RBWS-1515D VO				14.7	36.35			
UL RBWS-2020D VO	2.0	20		19.7	45.03			
UL RBWS-1TD-V0 BK	1.8	11	6.3	4.9	29.21			

UL ...UL1565 recognized product

(Unit : mm)

Slide and remove

Reusable Snap (Slide type)

Easy Operation!



Simply slide the body to install and remove. (Above photo is D type)

Space saving

Greatly reduces the snap protrusion on the underside of PCB
Also suitable for application in limited spaces.

Round hole mounting



No odd-shaped hole required
Drilling 3 holes only.