



Round inner corners also suitable for halogen-free cables

Releasable cable clamp with minimum protrusion on panel

Features

- Lock fastens and releases cables quickly.
- Detachable with no tools required.

Material

- Nylon 66 (Color : Natural, Black*)



Twist Type




Odd-shaped hole


UL94 V-0

* Black product has "BK" at the end of the part No.

Specification drawing



* 13mm for RBWS-1.5TL-VO BK



Part No.	(A)	B	(C)	Mounting hole size	Panel thickness	Std. Package
RBWS-1T-VO	28.2	4.9	5.3	Refer to Specification drawing	0.8~1.6	500 pcs.
RBWS-3T-VO	33.7	9.9	5.8			

Part No.	(A)	B	(C)	Mounting hole size	Panel thickness	Std. Package
RBWS-1TL-VO BK	28.6	4.9	5.7	Refer to Specification drawing	0.8~2.0	500 pcs.
RBWS-1.5TL-VO BK	32.0	6.4	5.7			
RBWS-2TL-VO BK	31.6	7.4	6.2			
RBWS-3TL-VO BK	34.1	9.9	6.2			

(Unit : mm)



Turn and remove


Reusable Snap (Twist type)



Space saving

Twist type

Conventional type



The snap protrusion is greatly reduced

Compared to conventional snap, the protrusion of snap is greatly lowered for application in limited spaces.

Easy Operation!

For installation and removal, simply turn the body

Can be removed from mounting side with no tool needed, while conventional snap requires cutting by nippers etc from the backside of the panel.