

Releasable cable clamp that provides a secure lock

Features

- Snap mounting provides easy maintenance and disassembling with no tools required.
- Both twist type and push type are available for easy dismount.

Material

- Nylon 66 (Color : Natural)

UL94 V-0



Twist Type



Odd-shaped hole

RLWS-T, TL





Push Type



Round hole

RLWS-S

RLWS-T





Part No.	(A)	(B)	(C)	D	Mounting hole size	Panel thickness	Std. Package
UL RLWS-1T V0	29.1	4.9	5.3	1.5	Refer to Specification drawing	0.8~1.6	1,000 pcs.
UL RLWS-2T V0	32.8	7.4	5.7	2			500 pcs.
UL RLWS-3T V0	35.6	9.9	5.8				

UL ...UL1565 recognized product

(Unit : mm)

Specification drawing





Part No.	(A)	B	C	Mounting hole size	Panel thickness	Std. Package
UL RLWS-1015T V0	32.84	10.4	15	Refer to Specification drawing	0.8~1.6	500 pcs.
UL RLWS-1515T V0	37.84	15.4				
UL RLWS-2020T V0	46.37	20.4				

UL ...UL1565 recognized product

(Unit : mm)

RLWS-TL




Part No.	(A)	B	C	Mounting hole size	Panel thickness	Std. Package
UL RLWS-0510TL V0	26.00	5.4	10	Refer to Specification drawing	0.8~3.2	500 pcs.
UL RLWS-1010TL V0	31.00	10.4				
UL RLWS-1515TL V0	39.54	15.4				
UL RLWS-2020TL V0	48.07	20.4				

UL ...UL1565 recognized product

(Unit : mm)

RLWS-S



Part No.	(A)	B	C	D	Mounting hole size	Panel thickness	Std. Package
UL RLWS-1S V0	32.8	6.4	1.5	1.5	$\phi 4.8^{+0.1}$	0.5~1.6	1,000 pcs.
UL RLWS-3S V0	39.4	11.9	2.0	2.0			

UL ...UL1565 recognized product

(Unit : mm)

\* (19.5)mm for RLWS-1S V0